



EFA 820 S4 240 Hybrid

Order No. **716288**

Main features

Light output [W]	960
Light source / lamps	LED - 4 × 240 W
Illumination range (5 lux min.) [m ²]	3100
Light flux (Lumens) approx. [lm]	139.200
Mast	340° rotatable
Insulation class [IP]	23
Nominal voltage [V]	230
Sound pressure level LPA (7 m) [db(A)]	0-58
Max. light spot height (m)	8,2
Min. transport height (m)	2,42
Dimensions L x W x H [mm]	2245 x 1431 x 2424
Weight in kg ca.	1146

Operation

Trailer drawbar	height adjustable
Inertial brake	ja
Lifting system	Hydraulisch
Battery charging time [h]	4h 29'
Battery runtime [h]	min. 3h 45', max. 19h 46'
Mains supply socket	1x CEE 230 V / 16 A
Shockproof sockets	1x CEE 230 V / 16 A

Engine

Brand	Yanmar
Engine Type	2TNV70
Cooling system	Water-cooled
Displacement [ccm]	570
RPM [U/min]	1500
Fuel	Diesel
Fuel tank capacity [l]	100 (net. 90)
Starting system	Electric starter

Technical data and illustrations are not binding. We assume no liability for misprints.

2025-7-21

ENDRESS Elektrogerätebau GmbH
 Neckartenzlinger Str. 39
 D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
 Fax.: +49 (0) 7123-9737-50
www.endress-generator.com



EFA 820 S4 240 Hybrid

Order No. 716288



Equipment features

A maintenance-free aluminium telescopic mast

Forklift pockets integrated

Central crane loading lug

Simple and rapidly adjustable parking stand

A compact and robust construction

Simple to operate control unit - all functions can be actuated over a control panel

Large tank for long running times (Hybrid up to 471h)

Ideal for illumination during large events

A twilight sensor is installed as standard

Wind speed resistance 110 km/h

Earthing kit

Special equipment - not retrofittable

Order No.

Preheating System

341 508

Insulation Monitoring

341 509

laboratorio-olosuhteissa tehdyssä kiinteässä testisyklissä, eikä se ole tae yksittäisen moottorin suorituskyvystä".

Technical data and illustrations are not binding. We assume no liability for misprints.

2025-7-21

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generator.com

