



EMP 205

Order No. **411013**

Main features	
Max. delivery rate	600 l/min (36 m ³ /h)
Max. suction lift	8 m
Max. total delivery height	28 m
Solids Ø	4,5 mm
Connection S/D	2" / 2"
Ash seal	Alumina Porzellan
Weight in kg ca.	24
Dimensions L x W x H [mm]	477 x 395 x 410

Engine	
Engine Type	ENDRESS E210
Design	1-cylinder, 4-stroke, OHV
Displacement [ccm]	212
Output at 3600 rpm [kW]	4,4
Fuel	Petrol
Fuel tank capacity [l]	3,6
Running time @ 75% PRP	2
Starting system	Recoil starter
Sound power level LWA [db(A)]	102
Sound pressure level LPA (7 m) [db(A)]	80

Equipment features	
High flow rates	
Premium seals	
Lack of oil automatic switch-off	
3 x hose clips	
2 x hose couplings	
1 x strainer	
1 x spark plug wrench	
2 x seal for hose coupling	
2x hose connection	

Technical data and illustrations are not binding. We assume no liability for misprints.

2025-7-21

ENDRESS Elektrogerätebau GmbH
 Neckartenzlinger Str. 39
 D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
 Fax.: +49 (0) 7123-9737-50
www.endress-generator.com



EMP 205

Order No. 411013



Accessories

Suction hose 2" 8 m (with quick-release coupling)
Pressure hose 2" 15 m (with quick-release coupling)
Pressure hose extension 2" 10 m (with quick-release coupling)

Order No.

38 410
38 411
38 414

laboratorio-olosuhteissa tehdyssä kiinteässä testisyklissä, eikä se ole tae yksittäisen moottorin suorituskyvystä".

Technical data and illustrations are not binding. We assume no liability for misprints.

2025-7-21

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generator.com

