



EMP 305 ST

Order No. **411015**

Main features

Max. delivery rate	1100 l/min (66 m ³ /h)
Max. suction lift	7 m
Max. total delivery height	26 m
Solids Ø	28 mm
Connection S/D	3" / 3"
Ash seal	Silikon-Karbid
Weight in kg ca.	35
Dimensions L x W x H [mm]	552 x 432 x 450

Engine

Engine Type	ENDRESS E210
Design	1-cylinder, 4-stroke, OHV
Displacement [ccm]	212
Output at 3600 rpm [kW]	4,4
Fuel	Petrol
Fuel tank capacity [l]	3,6
Running time @ 75% PRP	2
Starting system	Recoil starter
Sound power level LWA [db(A)]	109
Sound pressure level LPA (7 m) [db(A)]	87

Equipment features

High flow rates
Premium seals
Lack of oil automatic switch-off
3 x hose clips
2 x hose couplings
1 x strainer
1 x spark plug wrench
2 x seal for hose coupling
2x hose connection

Technical data and illustrations are not binding. We assume no liability for misprints.

2025-7-21

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generator.com



EMP 305 ST

Order No. 411015



Accessories	Order No.
Suction hose 3" 8 m (with quick-release coupling)	38 407
Pressure hose 3" 15 m (with quick-release coupling)	38 408
Pressure hose extension 3" 10 m (with quick-release coupling)	38 409

laboratorio-olosuhteissa tehdyssä kiinteässä testisyklissä, eikä se ole tae yksittäisen moottorin suorituskyvystä".

Technical data and illustrations are not binding. We assume no liability for misprints.

2025-7-21

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generator.com

