



ESE 510 VW/AS

Order No. **321261**

Main features

Emergency Standby Power (ESP) [kVA/kW]	509.7/407.8
Prime power (PRP) [kVA/kW]	458.8/367.0
Nominal voltage [V]	400/230
Frequency [Hz]	50
Nominal current 3~ (PRP) [A]	662
Power factor cos (phi)	0,8

Measures and weight

Dimensions L x W x H [mm]	4000 x 1460 x 2147
Weight in kg ca.	4326
Fuel tank capacity [l]	650

Autonomy

Running time @ 75% PRP [h]	9,37
----------------------------	------

Noise level

Sound power level LWA [db(A)]	98
Sound pressure level LPA (7 m) [db(A)]	73

Technical data and illustrations are not binding. We assume no liability for misprints.

2025-9-12

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generator.com



ESE 510 VW/AS

Order No. 321261



Motor	
Brand	Volvo
Model	TAD1345GE
Emission regulation	Stage II
Nr. of cylinder and disposition	6L
Cooling system	Water-cooled
Displacement [ccm]	12780
Engine output (ESP) [kW]	441
Engine output (PRP) [kW]	398
RPM [U/min]	1500
RPM regulation	electronic
Starting system	Electric starter
Electric circuit [V]	24
Fuel	Diesel
Specific fuel consumption @ 75% PRP [g/kWh]	194
Oil capacity [L]	36
Coolant capacity [L]	44
Fuel consumption @ 75% PRP [L/h]	69,37
Fuel consumption @ 100% PRP [L/h]	91,43

LTP - Limited Power in continuous service as ISO 8528-1:2005. It is defined as the maximum power available, under the agreed operating conditions, for which the generating set is capable of delivering for up to 500 h of operation per year (whose no more than 300 for continuative use) with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. No overload capability is available.

PRP - Power in continuous service as ISO 8528-1:2005. It is defined as being the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load when operated for an unlimited number of hours per year under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturer. The permissible average power output over 24h of operation shall not exceed 70 % of the prime power.

COP - Base load (continuous) service as ISO 8528-1:2005. It is defined as being the maximum power which the generating set is capable of delivering continuously whilst supplying a constant electrical load when operated for an unlimited number of hours per year under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturer. A 10% overload capacity is available for a period of 1 hour within a 12-hour period of operation.

Ratings definition (ISO-8528)

ESP - Emergency Standby Power: It is the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200 h of operation per year with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. The permissible average power output over 24 h of operation shall not exceed 70 % of the ESP.

This CO₂ measurement results from testing over a fixed test cycle under laboratory conditions a(n) (parent) engine representative of the engine type (engine family) and shall not imply or express any guarantee of the performance of a particular engine'.

laboratorio-olosuhteissa tehdyssä kiinteässä testisyklissä, eikä se ole tae yksittäisen moottorin suorituskyvystä".

Technical data and illustrations are not binding. We assume no liability for misprints.

2025-9-12

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generator.com



ESE 510 VW/AS

Order No. 321261

Generator	
Brand	Mecc Alte ECO40 3S4 C
Alternator type	ECO40 3S4 C
Insulation class	H
Protection Class [IP]	23
Poles	4
Frequency [Hz]	50
Voltage tolerance [%]	0,5
Power factor cos (phi)	0,8
Efficiency @ 100% load [%]	94,6

Equipment features	
Automatic control panel with digital control	
Problem-free use, also in winter through use of a standard engine and coolant prewarming	
Electronic Engine Governor	
Terminal board	
Manual oil scavenger pump	
Liquid collecting tray to protect the environment	

Special equipment - not retrofittable	Order No.
Crane loading lug	auf Anfrage
Winding Total Protection	auf Anfrage
Metal Fuel tank 2000l (incl. liquid collection tray)	auf Anfrage
Metal Fuel tank 4000l (incl. liquid collection tray)	auf Anfrage
Automatic fuel pump	auf Anfrage
Extra Silent Enclosure	auf Anfrage
Galvanized base frame with integrated forklift pockets	auf Anfrage
Exhaust Spark Arrestor	auf Anfrage
→ E-RMA SIM remote monitoring	342 228
→ E-RMA LAN remote monitoring	342 229

Accessories	Order No.
Load transfer switch / E-US 800	343 027

Technical data and illustrations are not binding. We assume no liability for misprints.

2025-9-12

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generator.com

