

ENDRESS®

Power Generators

ESE 604 DHG DIN

Order No. **156001KI**

Main features	
Alternator type	**Duplex**
Continuous Power 3~ [kVA/kW]	6.0/4.8
Continuous Power 1~ [kVA/kW]	4.0/3.6
Nominal voltage [V]	400/230
Nominal Current [A]	8.7/17.4
Power factor cos (phi)	0,8
Frequency [Hz]	50
Protection Class [IP]	54

Engine	
Engine Type	HONDA GX390 / 11 HP
Design	1-cylinder 4-stroke OHV
Displacement [ccm]	389
Output 3000 rpm	6,4
CO2 emissions [g / kWh]	743
CO2 test procedure	k.A
Fuel	Petrol
Fuel tank capacity [l]	6,5
Running time @ 75% PRP	3,4
Starting system	Recoil starter
Weight in kg ca.	95
Dimensions L x W x H [mm]	700 x 440 x 580
Shockproof sockets	3 x 230V 16A 1x CEE 400V 16A

This CO2 measurement results from testing over a fixed test cycle under laboratory conditions a(n) (parent) engine representative of the engine type (engine family) and shall not imply or express any guarantee of the performance of a particular engine'.

Advantages at a glance

- Comprehensive functions, safe and simple operation
- ➔ DUPLEX current quality without compromise
- Special equipment and accessories, available for many requirements
- Fitted according to DIN 14685-1
- Multifunctional control display E-MCS 4.0 - a clear system

Power ratings according to ISO 8528-1: 2005

Technical data and illustrations are not binding. We assume no liability for misprints.

2024-11-4

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generators.de

A PART OF PRETTL

ESE 604 DHG DIN

Order No. 156001KI

Equipment features
Insulation monitoring – without shut-off
3-way fuel cock for external refuelling
Multifunction control display E-MCS 4.0
Lack of oil automatic switch-off
Alternator overload protection
Folding handles
Vehicle tool kit

Special equipment - not retrofittable	Order No.
Insulation monitoring device with shut-off	163 071
Special colour	auf Anfrage

Accessories	Order No.
Exhaust hose (1.5 m)	**163 120**
Exhaust hose (2.5 m)	**163 121**
90° Adapter for Exhaust hose	**163 130**
Refueling system for 3-way fuel valve	**163 110**
Hose for refuelling without a canister	**E100 592**
Wheel Kit for the 5 and 8 series DIN frame with folding handle	**163 103**

Power ratings according to ISO 8528-1: 2005

Technical data and illustrations are not binding. We assume no liability for misprints.

2024-11-4

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generators.de

A PART OF PRETTL