

ESE 904 DBG ES DIN

Order No. **151013KI**

Main features	
Alternator type	**Duplex**
Continuous Power 3~ [kVA/kW]	9.0/7.2
Continuous Power 1~ [kVA/kW]	6.0/5.4
Nominal voltage [V]	400/230
Nominal Current [A]	12.9/26.1
Power factor cos (phi)	0,8
Frequency [Hz]	50
Protection Class [IP]	54

Engine	
Engine Type	B&S Vanguard 16 HP
Design	2-cylinder. 4-stroke OHV
Displacement [ccm]	479
Output 3000 rpm	9,5
CO2 emissions [g / kWh]	927,21
CO2 test procedure	G1
Fuel	Petrol
Fuel tank capacity [l]	12
Running time @ 75% PRP	5
Starting system	Electric starter
Weight in kg ca.	136
Dimensions L x W x H [mm]	820 x 440 x 580
Shockproof sockets	3 x 230V 16A 1 x 400V CEE 16A

This CO2 measurement results from testing over a fixed test cycle under laboratory conditions a(n) (parent) engine representative of the engine type (engine family) and shall not imply or express any guarantee of the performance of a particular engine'.

Power ratings according to ISO 8528-1: 2005

Technical data and illustrations are not binding. We assume no liability for misprints.

2025-7-10

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generators.de

ESE 904 DBG ES DIN

Order No. 151013KI

Advantages at a glance
Comprehensive functions, safe and simple operation
DUPLEX current quality without compromise
Special equipment and accessories, available for many requirements
Fitted according to DIN 14685-1
Multifunctional control display E-MCS 4.0 - a clear system
Large fuel tank for long operation – without refuelling
Emergency start function over the recoil starter

Equipment features
Insulation monitoring – without shut-off
3-way fuel valve for external refuelling
Multifunction control display E-MCS 4.0
Fuel level indicator over the E-MCS 4.0
Lack of oil automatic switch-off
Alternator overload protection
Starter battery 12 V/20 A
Folding handles
Spark plug wrench

Special equipment - not retrofittable	Order No.
FireCAN	163 140
Automatik Choke	163 030
Remote start device	163 150
Beos charging current socket	163 080
Charging current socket DIN 14690	163 010
Charging current socket MagCode	163 018
External start Nato socket	163 000
Insulation monitoring device with shut-off	163 071
ECOtronic System	163 020
Special colour	auf Anfrage

Accessories	Order No.
Exhaust hose (1.5 m)	163 120
Exhaust hose (2.5 m)	163 121
90° Adapter for Exhaust hose	163 130
Refueling system for 3-way fuel valve	163 110
Hose for refuelling without a canister	E100 592
Wheel Kit for the 5 and 8 series DIN frame with folding handle	163 103
Maintenance kit	auf Anfrage

Power ratings according to ISO 8528-1: 2005

Technical data and illustrations are not binding. We assume no liability for misprints.

2025-7-10

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generators.de