



ESE 907 DBG DIN Super Silent

Order No. **156203**

Main features

Alternator type	Duplex
Continuous Power 3~ [kVA/kW]	9.0/7.2
Continuous Power 1~ [kVA/kW]	6.0/5.4
Nominal voltage [V]	400/230
Nominal Current [A]	12.9/26.1
Power factor cos (phi)	0,8
Frequency [Hz]	50
Protection Class [IP]	54

Engine

Engine Type	B&S Vanguard 16 HP
Design	2-cylinder. 4-stroke OHV
Displacement [ccm]	479
Output 3000 rpm	9,5
CO2 emissions [g / kWh]	927,21
CO2 test procedure	G1
Fuel	Petrol
Fuel tank capacity [l]	22
Running time @ 75% PRP	9,2
Starting system	Recoil starter
Weight in kg ca.	130
Dimensions L x W x H [mm]	820 x 440 x 580
Shockproof sockets	3 x 230V 16A 1 x 400V CEE 16A

This CO2 measurement results from testing over a fixed test cycle under laboratory conditions a(n) (parent) engine representative of the engine type (engine family) and shall not imply or express any guarantee of the performance of a particular engine'.

Power ratings according to ISO 8528-1: 2005

Technical data and illustrations are not binding. We assume no liability for misprints.

2026-7-2

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generator.com



ESE 907 DBG DIN Super Silent

Order No. 156203



Advantages at a glance

- Comprehensive functions, safe and simple operation
- DUPLEX current quality without compromise
- Special equipment and accessories, available for many requirements
- Fitted according to DIN 14685-1
- Multifunctional control display E-MCS 4.0 - a clear system
- Large fuel tank for long operation – without refuelling

Equipment features

- Insulation monitoring – without shut-off
- 3-way fuel valve for external refuelling
- Multifunction control display E-MCS 4.0
- Fuel level indicator over the E-MCS 4.0
- Lack of oil automatic switch-off
- Alternator overload protection
- Folding handles
- Spark plug wrench

Special equipment - not retrofittable

Order No.

- Insulation monitoring device with shut-off 163 071
- ECOtronic System 163 020
- Colour red RAL 3000 163 180
- Exhaust gas routing on panel side 163 905
- Supplying power to a building IT/TN 162 050

Accessories

Order No.

- Exhaust hose (1.5 m) **163 120**
- Exhaust hose (2.5 m) **163 121**
- 90° Adapter for Exhaust hose **163 130**
- Refueling system for 3-way fuel valve **163 110**
- Hose for refuelling without a canister **E100 592**
- Wheel Kit for the 5 and 8 series DIN frame with folding handle **163 103**
- Maintenance kit auf Anfrage

laboratorio-olosuhteissa tehdyssä kiinteässä testisyklissä, eikä se ole tae yksittäisen moottorin suorituskyvystä".

Power ratings according to ISO 8528-1: 2005

Technical data and illustrations are not binding. We assume no liability for misprints.

2026-7-2

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generator.com

