



## EZG 40/4 II/TN-S

Order No. **511504**

### Main features

Variant feed mode

### Alternator

Continuous output [kVA/kW]	40.0/32.0
Nominal voltage [V]	400/230
Voltage regulation	AVR
Nominal Current [A]	57,7 3~
Frequency [Hz]	50
Protection Class [IP]	44/54
Recommended tractor power output approx. [HP]	80
Nominal speed of power take-off shaft	430
Category 3-point suspension	2
PTO connection type	1"3/8 Z6
Weight in kg ca.	315
Dimensions L x W x H [mm]	1065 x 736 x 1031
Socket combination	3 x 230 V/16 A 1 x CEE 400 V/16 A 1 x CEE 400 V/32 A 1 x CEE 400 V/63 A 1 x CEE 400 V/63 A, 1 h

### Advantages at a glance

Fulfilment of the requirements of the Agricultural Employer's Liability Insurance Association

Switching option operation in the field / feed into a building (IT/TN network)

Insulation monitoring during operation in the field - safe mobile operation

Protection over the building installation in power feed operation (TN network)

Mains supply socket CEE 5-pin, 1 h designed for the maximum power output of the alternator

EZG 40/4 II/TN-S

Order No. 511504



**Equipment features**

Fuses over an all-phase line circuit breaker

Incl. 3-point suspension Category 2

Operating hours counter

Monitoring and display of frequency and voltage

Automatic safety switch-off

Large control lamps simplify adjustment of the power take-off shaft rotational speed (traffic lights function)

A robust steel frame with forklift pockets

Development and manufacture in Germany

**Accessories**

**Order No.**

Wheel kit

**161 036**

Adapter for category 3

**162 048**

Extension for lower link / upper link

162 047

Supply connector, CEE 400 V / 63A, 1 h

E 135 847

CEE Feed-in cable IT/TN 1h plug -> 1h coupling - CEE 400V / 63A 5m

343 038

CEE Feed-in cable IT/TN 1h plug -> 1h coupling - CEE 400V / 63A 10m

343 037

laboratorio-olosuhteissa tehdyssä kiinteässä testisyklissä, eikä se ole tae yksittäisen moottorin suorituskyvystä".

Technical data and illustrations are not binding. We assume no liability for misprints.

2025-7-25

**ENDRESS Elektrogerätebau GmbH**  
Neckartenzlinger Str. 39  
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0  
Fax.: +49 (0) 7123-9737-50  
www.endress-generator.com

