



Imagen semejante /
Illustration similar

ENDRESS

Power Generators

ESE 1290 CW/AS

Order No. **87533006**

Main features

Max. Output [LTP] [kVA/kW]	1265/1012
Prime power (PRP) [kVA/kW]	1150/920
Nominal voltage [V]	480/277
Frequency [Hz]	60
Nominal current 3~ (PRP) [A]	1521,56
Power factor cos (phi)	0,8
Main circuit breaker [Pole]	4

Measures and weight

Dimensions L x W x H [mm]	6941 x 2171 x 2679
Weight in kg ca.	9515
Fuel tank capacity [l]	500

Noise level

Sound power level LWA [db(A)]	113
Sound pressure level LPA (7 m) [db(A)]	75

Installation data

Total air flow [m ³ /min]	60
Exhaust gas flow @ LTP [m ³ /min]	178,8
Exhaust gas temperature @ LTP [°C]	525
Maximum back pressure [kPa]	8,5

Motor

Brand	Cummins
Model	QST30-G4

Technical data and illustrations are not binding. We assume no liability for misprints.

2023-11-9

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generators.de



ESE 1290 CW/AS

Order No. 87533006



Power Generators

Generator	
Brand	MeccAlte ECO43-1L/4
Alternator type	synchron
Insulation class	Klasse H
Voltage regulation	electronic
Protection Class [IP]	21
Poles	4
Frequency [Hz]	60
Frequency tolerance [%]	±1
Voltage tolerance [%]	1
Power factor cos (phi)	0,8
Efficiency @ 75% load [%]	96,1
Standard AVR	DSR
THD full load LL/LN [%]	1,5 / 1,7
THD no load LL/LN [%]	2,1 / 2,1
THF [%]	<2
Short Circuit Current Capacity [%]	>300

of the performance of a particular engine'.

Technical data and illustrations are not binding. We assume no liability for misprints.

2023-11-9

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generators.de

