



# ENDRESS

## Power Generators

### ESE 1520 CW/AS

Order No. **87533007**

#### Main features

Max. Output [LTP] [kVA/kw]	1520,71/1216,57
Prime power (PRP) [kVA/kw]	1377,32/1101,86
Nominal voltage [V]	480/277
Frequency [Hz]	60
Nominal current 3~ (PRP) [A]	1829,13
Power factor cos (phi)	0,8
Main circuit breaker [Pole]	4

#### Measures and weight

Dimensions L x W x H [mm]	7800 x 2424 x 2997
Weight in kg ca.	11579
Fuel tank capacity [l]	500

#### Noise level

Sound power level LWA [db(A)]	113
Sound pressure level LPA (7 m) [db(A)]	97

#### Installation data

Total air flow [m <sup>3</sup> /min]	108
Exhaust gas flow @ LTP [m <sup>3</sup> /min]	312
Exhaust gas temperature @ LTP [°C]	535
Maximum back pressure [kPa]	8,5

#### Motor

Brand	Cummins
Model	KTA50-G3

Technical data and illustrations are not binding. We assume no liability for misprints.

2023-11-9

ENDRESS Elektrogerätebau GmbH  
Neckartenzlinger Str. 39  
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0  
Fax.: +49 (0) 7123-9737-50  
www.endress-generators.de



ESE 1520 CW/AS

Order No. 87533007



**Power Generators**

Generator	
Brand	MeccAlte ECO43-2LN/4
Alternator type	synchron
Insulation class	Klasse H
Voltage regulation	electronic
Protection Class [IP]	21
Poles	4
Frequency [Hz]	60
Frequency tolerance [%]	±1
Voltage tolerance [%]	1
Power factor cos (phi)	0,8
Efficiency @ 75% load [%]	96,3
Standard AVR	DSR
THD full load LL/LN [%]	1,5 / 1,5
THD no load LL/LN [%]	2,4 / 2,4
THF [%]	<2
Short Circuit Current Capacity [%]	>300

of the performance of a particular engine'.

Technical data and illustrations are not binding. We assume no liability for misprints.

2023-11-9

**ENDRESS Elektrogerätebau GmbH**  
Neckartenzlinger Str. 39  
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0  
Fax.: +49 (0) 7123-9737-50  
[www.endress-generators.de](http://www.endress-generators.de)

