



# ENDRESS

## Power Generators

### ESE 275 PW/AS

Order No. **87523030**

#### Main features

Max. Output [LTP] [kVA/kw]	329/263,2
Prime power (PRP) [kVA/kw]	297/237,6
Nominal voltage [V]	480/277
Frequency [Hz]	60
Nominal current 3~ (PRP) [A]	395,73
Power factor cos (phi)	0,8
Main circuit breaker [Pole]	4

#### Measures and weight

Dimensions L x W x H [mm]	3951 x 1438 x 2085
Weight in kg ca.	2934
Fuel tank capacity [l]	636

#### Noise level

Sound power level LWA [db(A)]	97
Sound pressure level LPA (7 m) [db(A)]	68

#### Installation data

Total air flow [m <sup>3</sup> /min]	19,8
Exhaust gas flow @ LTP [m <sup>3</sup> /min]	48,9
Exhaust gas temperature @ LTP [°C]	496
Maximum back pressure [kPa]	10,2

#### Motor

Brand	Perkins
Model	1506A-E88TAG3

Technical data and illustrations are not binding. We assume no liability for misprints.

2023-11-9

**ENDRESS Elektrogerätebau GmbH**  
 Neckartenzlinger Str. 39  
 D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0  
 Fax.: +49 (0) 7123-9737-50  
[www.endress-generators.de](http://www.endress-generators.de)



ESE 275 PW/AS

Order No. 87523030



**Power Generators**

Generator	
Brand	MeccAlte ECO38-1LN/4
Alternator type	synchron
Insulation class	Klasse H
Voltage regulation	electronic
Protection Class [IP]	23
Poles	4
Frequency [Hz]	60
Frequency tolerance [%]	±1
Voltage tolerance [%]	1
Power factor cos (phi)	0,8
Efficiency @ 75% load [%]	94,5
Standard AVR	DSR
THD full load LL/LN [%]	2 / 2,1
THD no load LL/LN [%]	2,9 / 3,1
THF [%]	<2
Short Circuit Current Capacity [%]	>300

of the performance of a particular engine'.

Technical data and illustrations are not binding. We assume no liability for misprints.

2023-11-9

**ENDRESS Elektrogerätebau GmbH**  
Neckartenzlinger Str. 39  
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0  
Fax.: +49 (0) 7123-9737-50  
[www.endress-generators.de](http://www.endress-generators.de)

