

**ENDRESS** **Power Generators****ESE 515 PW/AS**Order No. **87523047****Main features**

Max. Output [LTP] [kVA/kW]	584/467,2
Prime power (PRP) [kVA/kW]	531/424,8
Nominal voltage [V]	480/277
Frequency [Hz]	60
Nominal current 3~ (PRP) [A]	702,44
Power factor cos (phi)	0,8
Main circuit breaker [Pole]	4

**Measures and weight**

Dimensions L x W x H [mm]	3951 x 1438 x 2085
Weight in kg ca.	4500
Fuel tank capacity [l]	636

**Noise level**

Sound power level LWA [db(A)]	97
Sound pressure level LPA (7 m) [db(A)]	69

**Installation data**

Total air flow [m <sup>3</sup> /min]	38
Exhaust gas flow @ LTP [m <sup>3</sup> /min]	105,3
Exhaust gas temperature @ LTP [°C]	511
Maximum back pressure [kPa]	6,8

**Motor**

Brand	Perkins
Model	2506A-E15TAG3

Technical data and illustrations are not binding. We assume no liability for misprints.

2023-11-9

ENDRESS Elektrogerätebau GmbH  
Neckartenzlinger Str. 39  
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0  
Fax.: +49 (0) 7123-9737-50  
www.endress-generators.de



ESE 515 PW/AS

Order No. 87523047



**Power Generators**

Generator	
Brand	MeccAlte ECO40-2S/4B
Alternator type	synchron
Insulation class	Klasse H
Voltage regulation	electronic
Protection Class [IP]	21
Poles	4
Frequency [Hz]	60
Frequency tolerance [%]	±1
Voltage tolerance [%]	1
Power factor cos (phi)	0,8
Efficiency @ 75% load [%]	95,5
Standard AVR	DSR
THD full load LL/LN [%]	2,5 / 2,6
THD no load LL/LN [%]	2,7 / 2,8
THF [%]	<2
Short Circuit Current Capacity [%]	>300

of the performance of a particular engine'.

Technical data and illustrations are not binding. We assume no liability for misprints.

2023-11-9

**ENDRESS Elektrogerätebau GmbH**  
Neckartenzlinger Str. 39  
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0  
Fax.: +49 (0) 7123-9737-50  
[www.endress-generators.de](http://www.endress-generators.de)

