



ENDRESS

Power Generators

ESE 760 MW/AS

Order No. **87523053**

Main features

Max. Output [LTP] [kVA/kw]	769,9/615,92
Prime power (PRP) [kVA/kw]	698,1/558,48
Nominal voltage [V]	480/277
Frequency [Hz]	60
Nominal current 3~ (PRP) [A]	926,05
Power factor cos (phi)	0,8
Main circuit breaker [Pole]	4

Measures and weight

Dimensions L x W x H [mm]	4700 x 1757 x 2430
Weight in kg ca.	5895
Fuel tank capacity [l]	636

Noise level

Sound power level LWA [db(A)]	109
Sound pressure level LPA (7 m) [db(A)]	79

Installation data

Total air flow [m ³ /min]	55
Exhaust gas flow @ LTP [m ³ /min]	136
Exhaust gas temperature @ LTP [°C]	461
Maximum back pressure [kPa]	15

Motor

Brand	MTU
Model	12V1600G20S

Technical data and illustrations are not binding. We assume no liability for misprints.

2023-11-9

ENDRESS Elektrogerätebau GmbH
 Neckartenzlinger Str. 39
 D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
 Fax.: +49 (0) 7123-9737-50
www.endress-generators.de



ESE 760 MW/AS

Order No. 87523053



Power Generators

Generator	
Brand	MeccAlte ECO40-1.5L/4
Alternator type	synchron
Insulation class	Klasse H
Voltage regulation	electronic
Protection Class [IP]	21
Poles	4
Frequency [Hz]	60
Frequency tolerance [%]	±1
Voltage tolerance [%]	1
Power factor cos (phi)	0,8
Efficiency @ 75% load [%]	96,3
Standard AVR	DSR
THD full load LL/LN [%]	2,2 / 2,4
THD no load LL/LN [%]	2,4 / 2,5
THF [%]	<2
Short Circuit Current Capacity [%]	>300

of the performance of a particular engine'.

Technical data and illustrations are not binding. We assume no liability for misprints.

2023-11-9

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generators.de

