ENDRESS
Together, always on.

ESE 206 HS-GT

Order No. 112300

Main features	
Alternator type	synchron
Max. Output 1~ [kVA/kW]	2.6/2.3
Continuous Power 1~ [kVA/kW]	2.0/1.8
Nominal voltage [V]	230
Nominal Current [A]	8,7
Power factor cos (phi)	0,9
Frequency [Hz]	50
Protection Class [IP]	23

Engine	
Engine Type	Honda GX 160 / 5HP
Displacement [ccm]	163
CO2 emissions [g / kWh]	757
CO2 test procedure	k.A
Fuel	Petrol
Fuel tank capacity [l]	20
Fuel consumption @ 75% PRP [L/h]	0,9
Running time @ 75% PRP	22,2
Starting system	Recoil starter
Sound power level LWA [db(A)]	96
Sound pressure level LPA (7 m) [db(A)]	71
Weight in kg ca.	41
Dimensions L x W x H [mm]	637 x 473 x 500
Shockproof sockets	2 x 230 V/16 A

This CO2 measurement results from testing over a fixed test cycle under laboratory conditions a(n) (parent) engine representative of the engine type (engine family) and shall not imply or express any guarantee of the performance of a particular engine'.

Equipment features
Lack of oil automatic switch-off
Alternator overload protection
Honda OHV engines
Large fuel tank for long running times

Power ratings according to ISO 8528-1: 2005

Technical data and illustrations are not binding. We assume no liability for misprints.

2026-10-12

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generator.com

ESE 206 HS-GT

Order No. 112300

Possible applications	230V
Electric tools up to	2100W
Gardening or construction equipment up to	1500W
Compressors or pumps up to	1100W

Special equipment - not retrofittable	Order No.
RCD protection switch incl. earthing kit	162 352

Accessories	Order No.
Wheel kit	**161 000**
Maintenance kit	**164 028**

laboratorio-olosuhteissa tehdyssä kiinteässä testisyklissä, eikä se ole tae yksittäisen moottorin suorituskyvystä".

Power ratings according to ISO 8528-1: 2005

Technical data and illustrations are not binding. We assume no liability for misprints.

2026-10-12

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generator.com