



ENDRESS

Power Generators

ESE 5500i

Order No. **110050**

Main features

Alternator type	synchron
Max. Output 1~ [kVA/kW]	6.0/6.0
Continuous Power 1~ [kVA/kW]	5.5/5.5
Nominal voltage [V]	120/240
Nominal Current [A]	45.8/22,9
Power factor cos (phi)	1
Frequency [Hz]	60
Protection Class [IP]	23

Engine

Engine Type	Endress 300i
Design	1-cylinder 4-stroke OHV
Displacement [ccm]	302
Fuel	Petrol
Fuel tank capacity [l]	16
Running time @ 75% PRP	6,7
Starting system	Electric starter
Sound pressure level LPA (7 m) [db(A)]	78
Weight in kg ca.	55
Dimensions L x W x H [mm]	605 x 514 x 537
Shockproof sockets	2 x 120V 1 x 120/240V 1 x 12V / 8,3 A

This CO₂ measurement results from testing over a fixed test cycle under laboratory conditions a(n) (parent) engine representative of the engine type (engine family) and shall not imply or express any guarantee of the performance of a particular engine'.

Advantages at a glance

Inverter technology
High-quality current
Easy handling
Compact

Power ratings according to ISO 8528-1: 2005

Technical data and illustrations are not binding. We assume no liability for misprints.

2024-6-18

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generators.de



ESE 5500i

Order No. 110050



Equipment features

Lack of oil automatic switch-off

Alternator overload protection

Variable speed constant frequency (VSCF)

Connection for a 12 V battery charge

Wheelset as standard

Foldable handle

Power ratings according to ISO 8528-1: 2005

Technical data and illustrations are not binding. We assume no liability for misprints.

2024-6-18

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generators.de

