



ENDRESS

Power Generators

EZG 40/4 II/TN-S

Order No. **511504**

Main features

Variant feed mode

Alternator

Continuous output [kVA/kW]	40.0/32.0
Nominal voltage [V]	400/230
Voltage regulation	AVR
Nominal Current [A]	57,7 3~
Personal protection	Insulation monitoring device
Frequency [Hz]	50
Protection Class [IP]	44/54
Recommended tractor power output approx. [HP]	80
Nominal speed of power take-off shaft	430
Category 3-point suspension	2
Weight in kg ca.	315
Dimensions L x W x H [mm]	1065 x 736 x 1031
Socket combination	3 x 230 V/16 A 1 x CEE 400 V/16 A 1 x CEE 400 V/32 A 1 x CEE 400 V/63 A 1 x CEE 400 V/63 A, 1 h

Advantages at a glance

- Fulfilment of the requirements of the Agricultural Employer's Liability Insurance Association
- Switching option operation in the field / feed into a building (IT/TN network)
- Personal protection. Insulation monitoring during operation in the field - safe mobile operation
- Protection over the building installation in power feed operation (TN network)
- Mains supply socket CEE 5-pin, 1 h designed for the maximum power output of the alternator

Technical data and illustrations are not binding. We assume no liability for misprints.

2024-6-21

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generators.de



EZG 40/4 II/TN-S

Order No. 511504



Power Generators

Equipment features

Fuses over an all-phase line circuit breaker

Operating hours counter

Monitoring and display of frequency, voltage, current

Automatic safety switch-off

Large control lamps simplify adjustment of the power take-off shaft rotational speed (traffic lights function)

A robust steel frame with forklift pockets

Development and manufacture in Germany

Accessories

Order No.

Wheel kit

161 036

Adapter for category 3

162 048

Supply connector, CEE 400 V / 63A, 1 h

E 135 847

Extension for lower link / upper link

162 047

of the performance of a particular engine'.

Technical data and illustrations are not binding. We assume no liability for misprints.

2024-6-21

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generators.de

